

## SANDMERE



[www.bespokebrick.com](http://www.bespokebrick.com)

01634 707707

[enquiries@bespokebrick.com](mailto:enquiries@bespokebrick.com)

Unit 1 Magazine B, Ordnance Yard, Upnor Road, Lower Upnor, Kent, ME2 4UY

Issue Date: January 2020

## PRODUCT INFORMATION

|           |                             |
|-----------|-----------------------------|
| Packaging | Shrink wrapped & palletised |
|-----------|-----------------------------|

## TECHNICAL INFORMATION

|                                 |                                  |
|---------------------------------|----------------------------------|
| Reaction to fire                | A1                               |
| Brick Dimensions (L x W x H)    | 215 x 102 x 65mm                 |
| Size Tolerances Mean & Range    | T2, R1                           |
| Configuration                   | Frogged                          |
| Voids                           | 20%                              |
| Mean Compressive Strength       | 15 N/mm <sup>2</sup>             |
| Active Soluble Salts            | S2                               |
| Water Absorption                | 24%                              |
| Durability                      | F2                               |
| Gross Dry Density               | 1,450 Kg/m <sup>3</sup>          |
| Equivalent Thermal Conductivity | 50/50 : 0.41 / 90/90 : 0.45 W/mK |
| Initial Rate of Absorption      | > 4 kg/(m <sup>2</sup> .min)     |